Elliptical ADCP Buoys

DeepWater Buoyancy understands the value of data recovery, as well as, ADCP technology, oceanographic operations and what it takes to supply products that ensure success.

Manufactured from high-performance DeepTec™ syntactic foam, adjustable urethane and UHMW instrument clamps, and 316L stainless steel and titanium hardware, DeepWater Buoyancy's ADCP Buoys are designed to outperform and outlast conventional mooring flotation.

Available with depth ratings to 6000 meters, they require minimal maintenance and are extremely durable under the most rigorous deepwater conditions.

Designed by an experienced engineering staff that fully understands the effects of mooring excursions on data quality, galvanic corrosion and biofouling, these buoys are performance-proven and have a long track record of successful deployment and recovery.

Elliptical ADCP buoys have lower drag for a given buoyancy than spherical buoy and significantly lower drag than glass or plastic spheres.



DIAMETER IN INCHES

		30	44	47	32	
	• •	• • • • • • •	• • • • • • • • •		•••••	
DEPTH		UPLIFT IN LBS/KG				
750		193/87	317/144	401/182	610/276	
1500	•	157/71	259/117	330/150	510/231	
3500	•	123/55	204/92	263/119	414/187	
6000	•	116/52	183/83	237/107	378/171	

11

Other depths and diameters available upon request.



Rising to your undersea challenges